


### MISSOURI DEPARTMENT OF HEALTH AND SENIOR SERVICES STATE PUBLIC HEALTH LABORATORY

BREATH ALCOHOL PROGRAM

#### INTOX DMT MAINTENANCE REPORT

REPORT #1

O 005 or less. Mark the box corresponding to the standard being used.  © 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE  0.08% STANDARD - MUST READ BETWEEN 0.038% AND 0.084% INCLUSIVE  1 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  FEST 1: 0.099  TEST 2: 0.100  TEST 3: 0.100  TEST 3: 0.100  TEST 3: 0.100  TEST 3: 0.100  OVER 19: 0  OVER 19: 0  OVER 19: 0  STANDING OFFICER  GRATURE  STANDING OFFICER  GRATURE  PRINT FULL NAME  BRYAN SILVERTHORN  PER PERBIT NUMBER  240012  PRINT FULL NAME  BRYAN SILVERTHORN  TELEPHONE NUMBER	Complete this repor	t wnenever the instrum	ilar monthly preventive main ent is serviced or repaired a 15 days to the Breath Alcoh	nd whenever it is plac	ed into served By Carol Day at 2:	:01 pm, Aug 25, 2015	
Cuba Police Department Cuba, Missouri  CHECKLIST, Pice a mark in the box by each tern if found to be satisfactory or is operating within established limits. (Write in observed without where determined). Unmarked items must be corrected before using instrument.  DIATE AND TIME _08/13/2015 14:16:11	500103	The second secon					
Wallets where determined. Unmarked terms must be corrected before using instrument.  DATE AND TIME _08/13/2015 14:16:11	Cuba Police Dep	r (street and cirg partment Cuba, Miss	ouri	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
DATE AND TIME _ 08/13/2015 14:16:11	CHECKLIST: Place values where determ	e a mark in the box by enined). Unmarked items	each item if found to be satis is must be corrected before t	factory or is operating using instrument.	y within established limits. ()	Write in observed	
© PROGRAM	☑ DIAGNOSTIC I	RECORD					
© SAMPLE CHAMBER 48.8°C	DATE AND TIM	E 08/13/2015 14:10	<u>6:11</u>	☑ DETECTOR	14.00		
ETURN COMPLETED REPORT TO THE STANDARD SIMULATOR STANDARD AND STAN	☑ PROGRAM			☑ FILTER 1			
PUMP	SAMPLE CI	HAMBER 48.8°C		☑ FILTER 2			
BREATH ANALYZER ACCURACY STANDARDS  □ SIMULATOR STANDARD  □ SIMULATOR STANDARD  □ SIMULATOR STANDARD  □ SIMULATOR STANDARD  □ SIMULATOR SIMULATOR STANDARD  □ SIMULATOR SIMULAT	☑ BREATH TUBE 45.4°C ☑ FILTER 3						
□ SIMULATOR STANDARD □ STANDARD SUPPLIER_INTOXIMETERS □ LOT # AG516801	☑ PUMP			☑ INTERNAL STANDARD			
STANDARD SUPPLIER_INTOXIMETERS  LOT # AG516801  EXP. DATE 06/17/2017  SIMULATOR TEMP (34°C ± 0.2°C)  SIMULATOR SN  SIMULATOR EXP DATE  CALIBRATION CHECK - (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of 005 or less. Mark the box corresponding to the standard being used.  □ 0.10% STANDARD - MUST READ BETWEEN 0.076% AND 0.105% INCLUSIVE □ 0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.05% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.05% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.05% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.05% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.05% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.05% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.05% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.05% STANDARD - MUS	BREATH ANALYZE	R ACCURACY STAN	NDARDS				
□ SIMULATOR TEMP (34°C ± 0.2°C) SIMULATOR SN SIMULATOR EXP DATE  □ CALIBRATION CHECK · (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard. All three tests must be within ±5% of the standard value and must have a spread of 0.05 or less. Mark the box corresponding to the standard being used. □ 0.10% STANDARD · MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.05% ON 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.05% ON 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.05% ON 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.042% INCLUSIVE □ 0.04% STANDARD · MUST READ BETWEEN 0.042% INCLUSIVE □ 0.042%	☐ SIMULATOR STANDARD ☐ COMPRESSED ETHANOL-GAS MIXTURE						
CALIBRATION CHECK : (ONLY ONE STANDARD IS TO BE USED PER MAINTENANCE REPORT) Run three tests using a standard, All three tests must be within ±5% of the standard value and must have a spread of 0.05 or less. Mark the box corresponding to the standard being used.      □ 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE     □ 0.08% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE     □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE     □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE     □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE     □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE     □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE      □ 0.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.044% INCLUSIVE      □ 0.04% STANDARD - MUST READ	STANDARD SU     SU     STANDARD SU     SU	PPLIER <u>INTOXIME</u> T	TERS LOT#	AG516801	EXP. DATE 0	EXP. DATE <u>06/17/2017</u>	
Of 005 or less. Mark the box corresponding to the standard being used.  © 0.10% STANDARD - MUST READ BETWEEN 0.095% AND 0.105% INCLUSIVE  0.08% STANDARD - MUST READ BETWEEN 0.076% AND 0.084% INCLUSIVE  10.04% STANDARD - MUST READ BETWEEN 0.038% AND 0.042% INCLUSIVE  FEST 1: 0.099  TEST 2: 0.100  TEST 3: 0	☐ SIMULATOR TEMP (34°C ± 0.2°C)		SIMULA	ATOR SN	SIMULATOR EXP DATE		
DEFORM R.F.I. TEST  NDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS: 0	⊠ 0.10% S □ 0.08% S	TANDARD - MUST RE TANDARD - MUST RE	EAD BETWEEN 0.095% AN EAD BETWEEN 0.076% AN	ND 0.105% INCLUSIN ND 0.084% INCLUSIN	/E		
NDICATE THE NUMBER OF BREATH TESTS IN THE FOLLOWING RANGES SINCE THE LAST MAINTENANCE REPORT:  REFUSALS: 0 004: 0 .0509: 0 .1014: 0 .1519: 0 OVER .19: 0  ISTAMM NEW PARTS AND DESCRIBE ANY ALTERATION OR MODERCATION THAT WAS MADE TO RESTORE THE RISTRUMENT TO OPERATE SATISFACTORILY AND WITHIN  NSPECTING OFFICER  GNATURE  GNATURE  GNATURE  BRYAN SILVERTHORN  PRINT FULL NAME BRYAN SILVERTHORN  PER I PERMIT NUMBER 240012  EXPIRATION OATE 01/21/2016  TELEPHONE NUMBER SOUTHEAST ALCOHOL Program, MO Department of Health and Senior Services Southeast District Office	FEST 1: 0.099		TEST 2: 0,100	TEST 2: 0,100		TEST 3: 0.100	
REFUSALS: 0 004: 0 .0509: 0 .1014: 0 .1519: 0 OVER .19: 0  IST ANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO CPERATE SATISFACTORILY AND WITHIN  INSPECTING OFFICER  GNATURE S. S. PRINTFULL NAME BRYAN SILVERTHORN  PRINTFULL NAME BRYAN SILVERTHORN  PRINTFULL NAME BRYAN SILVERTHORN  PRINTFULL NAME BRYAN SILVERTHORN  TELEPHONIE NUMBER 240012  EXPIRATION DATE SOutheast District Office	☑ PERFORM R.F.I.	TEST					
STANY NEW PARTS AND DESCRIBE ANY ALTERATION OR MODIFICATION THAT WAS MADE TO RESTORE THE INSTRUMENT TO OPERATE SATISFACTORILY AND WITHIN  WSPECTING OFFICER  GNATURE  GNATURE  GNATURE  GNATURE  FRINT FULL NAME  BRYAN SILVERTHORN  PER PERMIT NUMBER  240012  EXPIRATION DATE  01/21/2016  FILEPHONE NUMBER  SOUTHWAS AND DEPARTMENT OF DEPARTME	NDICATE THE NUI	MBER OF BREATH T	ESTS IN THE FOLLOWIN	IG RANGES SINCE	THE LAST MAINTENAN	ICE REPORT:	
PRINT FULL NAME BRYAN SILVERTHORN  PETURN COMPLETED REPORT TO THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office	•		1	1 · · · · · · · · · · · · · · · · · · ·		OVER .19: 0	
PRINT FULL NAME BRYAN SILVERTHORN  FELEPHONE NUMBER 01/21/2016  ETURN COMPLETED REPORT TO THE Breath Alcohol Program, MO Department of Health and Senior Services Southeast District Office	IST ANY NEW PARTS AND C STABLISHED LIMITS (USE C	ESCRIBE ANY ALTERATION OF THER S'DE IF NECESSARY)	R MODIFICATION THAT WAS MADE TO	RESTORE THE INSTRUMENT	TO CPERATE SATISFACTORILY AN	D Wifhin	
240012 EXPIRATION DATE O1/21/2016  EXPIRATION DATE O1/21/2		ER			THORN		
ETURN COMPLETED REPORT TO THE Breath Alcohol Program, MO Department of Health and Senior Services  Southeast District Office							
D 580 7898 (3-13) AN ECHALOPPOPHIANTWACEPOATAG ACTION COSTS	ETURN COMPLET	ED REPORT TO THE	Breath Alcohol Program, Southeast District Office 2875 James Blvd, Poplar	Bluff, MO 63901			



7 Fastgate Dr. • P.O. Box 790 • Jacksonville, IL 62651-0790 217-245-2183 • Fax: 217-243-7634 • www.imoproducts.com

#### **Certificate of Analysis**

Certificate ID:

5179

Part #

BAC105L080T

Cylinder Size:

105L

Lot Number:

17513080A5

Expiration:

7/1/2015

0.080 BAC (For use with breath alcohol testing instruments)

Contents:

105 Liters @ 1000 psig 70°F (21°C)

Component:

Concentration:

Accuracy:

Method:

**NDIR** 

Ethanol

Nitrogen

208.4 pps

Balance

+/- 0.002 or 2%

**BAC** whichever

is greater

\*NIST Standard Reference Material Cylinder No. CC157791 / Job No. 13029 Certified 184.3 µmol/mol Ethanol in Nitrogen for ILMO Products Co., Jacksonville, IL

Distributed by:

Specialty Gas Lab Tech

CMI Inc.

316 East Ninth Street Owensboro, KY 42303 Phone 866-835-0690

www.alcoholtest.com

07/09/13



#### STATE OF MISSOURI

DEPARTMENT OF HEALTH AND SENIOR SERVICES
BREATH ALCOHOL PROGRAM



### PERMIT TYPE II

## **BRIAN S SILVERTHORN**

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field service and repairs, and operate the following breath analyzer(s):

# DATAMASTER, INTOX DMT

for the determination of the alcoholic content of blood from a sample of expired air. Permit issued under the provisions of sections 577.020 through 577.041, RSMo and 306.111 through 306.119 RSMo.

DATE4/22/2014	won Se
NUMBER 240184	DIRECTOR OF STATE PUBLIC HEALT: I LABORATORY
ACTUACION ACTUAC	210.0 Voolenag
EXPIRES 4/22/2016	
IO 550-0771 (G-16)	DIRECTOR OF DEPARTMENT OF HEALTH AND SENIOR SERVICES

LAB 4 (RS-10)



Operator SILVERTHORN, BRIAN

Permit No 240184

Date Issued 4/22/2014 Date Expires 4/22/2016